

## ZAR® Wood Patch - Red Oak

Version number: REV 6.0  
Replaces version of: 2023-02-22 (REV 5)

Revision: 2023-12-15

### SECTION 1: Identification

#### 1.1 Product identifier

Trade name **ZAR® Wood Patch - Red Oak**  
Alternative number(s) 31041; UFI: JTS9-0X9R-X80P-TGVN  
31012; UFI: 7UR1-6XNH-Q80H-GGYJ  
31013; UFI: YE12-TXP7-C800-MN80

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses filler  
paint

#### 1.3 Details of the supplier of the safety data sheet

United Gilsonite Laboratories, Inc. - Sika  
1396 Jefferson Avenue  
Dunmore PA 18509  
United States

Telephone: +1 (570) 344-1202  
Telefax: (570) 969-7634  
e-mail: sales@ugl.com  
Website: <http://www.ugl.com/>

e-mail (competent person) Robin.Crossley@ugl.com (Robin Crossley)

#### 1.4 Emergency telephone number

Emergency information service 1-800-424-9300 Chemtrec (NORTH AMERICA)  
Emergency telephone number: outside office hours

### SECTION 2: Hazard(s) identification

#### 2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.4R	respiratory sensitization	1	Resp. Sens. 1	H334
A.4S	skin sensitization	1	Skin Sens. 1	H317
A.7	reproductive toxicity	1B	Repr. 1B	H360F

For full text of abbreviations: see SECTION 16.

#### 2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS08



## ZAR® Wood Patch - Red Oak

Version number: REV 6.0  
Replaces version of: 2023-02-22 (REV 5)

Revision: 2023-12-15

**- Hazard statements**

H317 May cause an allergic skin reaction.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H360F May damage fertility.

**- Precautionary statements**

P201 Obtain special instructions before use.  
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.  
P272 Contaminated work clothing must not be allowed out of the workplace.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P285 In case of inadequate ventilation wear respiratory protection.  
P302+P352 If on skin: Wash with plenty of water.  
P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.  
P308+P313 If exposed or concerned: Get medical advice/attention.  
P321 Specific treatment (see on this label).  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P342+P311 If experiencing respiratory symptoms: Call a poison center/doctor.  
P363 Wash contaminated clothing before reuse.  
P405 Store locked up.  
P501 Dispose of contents/container to industrial combustion plant.

**- Hazardous ingredients for labelling** Wood Dust, Barium diboron tetraoxide

**2.3 Other hazards**

Hazards not otherwise classified

Contains Wood Dust, 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance in a concentration of  $\geq 0.1\%$ .

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of  $\geq 0.1\%$ .

**SECTION 3: Composition/information on ingredients****3.1 Substances**

Not relevant (mixture)

**3.2 Mixtures**

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
Distillates (petroleum), hydro-treated light	CAS No 64742-47-8	1 - < 5	Acute Tox. 3 / H331 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226
Wood Dust		0.05 - < 1	Resp. Sens. 1 / H334 Skin Sens. 1 / H317 Carc. 1A / H350 STOT SE 3 / H335 STOT RE 1 / H372 cD / OSHA003
Quartz (SiO <sub>2</sub> )	CAS No 14808-60-7	0.05 - < 1	Carc. 1A / H350

**ZAR® Wood Patch - Red Oak**

Version number: REV 6.0  
Replaces version of: 2023-02-22 (REV 5)

Revision: 2023-12-15

Name of substance	Identifier	Wt%	Classification acc. to GHS
Barium diboron tetraoxide	CAS No 13701-59-2	0.05 - < 1	Acute Tox. 4 / H302 Acute Tox. 4 / H332 Eye Irrit. 2B / H320 Repr. 1B / H360F
1,2-benzisothiazol-3(2H)-one	CAS No 2634-33-5	< 0.05	Acute Tox. 4 / H302 Skin Irrit. 2 / H315 Eye Dam. 1 / H318 Skin Sens. 1 / H317

For full text of abbreviations: see SECTION 16.

**SECTION 4: First-aid measures****4.1 Description of first-aid measures****General notes**

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

**Following inhalation**

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

**Following skin contact**

Wash with plenty of soap and water.

**Following eye contact**

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

**Following ingestion**

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

**4.2 Most important symptoms and effects, both acute and delayed**

Symptoms and effects are not known to date.

**4.3 Indication of any immediate medical attention and special treatment needed**

none

**SECTION 5: Fire-fighting measures****5.1 Extinguishing media****Suitable extinguishing media**

Water spray, BC-powder, Carbon dioxide (CO<sub>2</sub>)

**Unsuitable extinguishing media**

Water jet

**5.2 Special hazards arising from the substance or mixture****Hazardous combustion products**

Nitrogen oxides (NO<sub>x</sub>), Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

**5.3 Advice for firefighters**

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

**ZAR® Wood Patch - Red Oak**

Version number: REV 6.0  
Replaces version of: 2023-02-22 (REV 5)

Revision: 2023-12-15

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

**6.2 Environmental precautions**

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

**6.3 Methods and material for containment and cleaning up**

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

**6.4 Reference to other sections**

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

**7.2 Conditions for safe storage, including any incompatibilities**

Control of the effects

Protect against external exposure, such as

frost

**7.3 Specific end use(s)**

See section 16 for a general overview.

## ZAR® Wood Patch - Red Oak

 Version number: REV 6.0  
 Replaces version of: 2023-02-22 (REV 5)

Revision: 2023-12-15

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
US	mica	12001-26-2	TLV®		0.1					r	ACGIH® 2023
US	mica	12001-26-2	PEL (CA)		3					r, less1silica	Cal/ OSHA PEL
US	mica	12001-26-2	REL		3 (10 h)					r, less1silica	NIOSH REL
US	silicates (less than 1% crystalline silica); mica	12001-26-2	PEL	706						less1silica, partml, r	29 CFR 1910.1000
US	calcium carbonate	1317-65-3	REL		10 (10 h)					i, natural	NIOSH REL
US	calcium carbonate	1317-65-3	REL		5 (10 h)					r, natural	NIOSH REL
US	limestone	1317-65-3	REL		10 (10 h)					i	NIOSH REL
US	limestone	1317-65-3	REL		5 (10 h)					r	NIOSH REL
US	limestone (calcium carbonate)	1317-65-3	PEL		15					i, dust	29 CFR 1910.1000
US	limestone (calcium carbonate)	1317-65-3	PEL		5					r, dust	29 CFR 1910.1000
US	quartz	14808-60-7	PEL (CA)		0.05					r	Cal/ OSHA PEL
US	silica, crystalline - quartz	14808-60-7	PEL		0.05					r	29 CFR 1910.1000
US	silica, crystalline - quartz	14808-60-7	REL		0.05 (10 h)					r, appx-A	NIOSH REL

#### Notation

appx-A	NIOSH Potential Occupational Carcinogen (Appendix A)
Ceiling-C	ceiling value is a limit value above which exposure should not occur
dust	as dust
i	inhalable fraction
less1silica	with less than 1 % free crystalline silica
natural	natural
partml	particles/ml
r	respirable fraction
STEL	short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA	time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours
	time-weighted average (unless otherwise specified)

## ZAR® Wood Patch - Red Oak

Version number: REV 6.0  
 Replaces version of: 2023-02-22 (REV 5)

Revision: 2023-12-15

### 8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

Physical state	liquid
Color	not determined
Particle	not relevant (liquid)
Odor	characteristic

#### Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	≥146 °C at 101.3 kPa
Flash point	100 °C at 1 atm
Evaporation rate	not determined
Flammability (solid, gas)	not relevant, (fluid)
Vapor pressure	≤3.7 kPa at 37.8 °C
Density	1.757 g/cm <sup>3</sup> at 20 °C

## ZAR® Wood Patch - Red Oak

Version number: REV 6.0  
Replaces version of: 2023-02-22 (REV 5)

Revision: 2023-12-15

Vapor density	this information is not available
Solubility(ies)	not determined
Partition coefficient	
- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	220 °C (auto-ignition temperature (liquids and gases))
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

#### 10.2 Chemical stability

See below "Conditions to avoid".

#### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

#### 10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

#### 10.5 Incompatible materials

Oxidizers

#### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

##### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

##### Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

##### Acute toxicity

Shall not be classified as acutely toxic.

## ZAR® Wood Patch - Red Oak

Version number: REV 6.0  
 Replaces version of: 2023-02-22 (REV 5)

Revision: 2023-12-15

Acute toxicity estimate (ATE) of components			
Name of substance	CAS No	Exposure route	ATE
Distillates (petroleum), hydrotreated light	64742-47-8	inhalation: vapor	>5.28 mg/l/4h
Barium diboron tetraoxide	13701-59-2	oral	850 mg/kg
Barium diboron tetraoxide	13701-59-2	inhalation: dust/mist	1.5 mg/l/4h
1,2-benzisothiazol-3(2H)-one	2634-33-5	oral	670 mg/kg

### Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

### Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

### Respiratory or skin sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

### Carcinogenicity

Shall not be classified as carcinogenic.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans			
Name of substance	CAS No	Classification	Number
Quartz (SiO <sub>2</sub> )	14808-60-7	1	

### Legend

1 Carcinogenic to humans

### Reproductive toxicity

May damage fertility.

### Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

## SECTION 12: Ecological information

### 12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

### 12.2 Persistence and degradability

Data are not available.

### 12.3 Bioaccumulative potential

Data are not available.



**ZAR® Wood Patch - Red Oak**

Version number: REV 6.0  
Replaces version of: 2023-02-22 (REV 5)

Revision: 2023-12-15

**12.4 Mobility in soil**

Data are not available.

**12.5 Results of PBT and vPvB assessment**

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance in a concentration of  $\geq 0.1\%$ .

**12.6 Endocrine disrupting properties**

Does not contain an endocrine disruptor (ED) in a concentration of  $\geq 0.1\%$ .

**12.7 Other adverse effects**

Data are not available.

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

**Remarks**

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

**SECTION 14: Transport information**

<b>14.1 UN number</b>	not subject to transport regulations
<b>14.2 UN proper shipping name</b>	not relevant
<b>14.3 Transport hazard class(es)</b>	none
<b>14.4 Packing group</b>	not assigned
<b>14.5 Environmental hazards</b>	non-environmentally hazardous acc. to the dangerous goods regulations
<b>14.6 Special precautions for user</b>	There is no additional information.
<b>14.7 Transport in bulk according to IMO instruments</b>	The cargo is not intended to be carried in bulk.

**Information for each of the UN Model Regulations****Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information**

Not subject to transport regulations.

**International Maritime Dangerous Goods Code (IMDG) - Additional information**

Not subject to IMDG.

**International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information**

Not subject to ICAO-IATA.

## ZAR® Wood Patch - Red Oak

Version number: REV 6.0  
Replaces version of: 2023-02-22 (REV 5)

Revision: 2023-12-15

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations specific for the product in question

##### National regulations (United States)

**Toxic Substance Control Act (TSCA)** not all ingredients are listed (ACTIVE)

##### Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
Quartz (SiO <sub>2</sub> )	14808-60-7		IARC Carcinogens - 1

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
Quartz (SiO <sub>2</sub> )		1095			1.0 %

- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
Quartz (SiO <sub>2</sub> )		A, *	

##### Legend

\* Substances which are regulated by OSHA as carcinogens; have been categorized by the ACGIH as either "human carcinogens" or "suspect of carcinogenic potential for man"; have been evaluated by the International Agency for Research on Cancer (IARC) and found to be carcinogens or potential carcinogens; or have been listed as a carcinogen or potential carcinogen in the Annual Report on Carcinogens published by the National Toxicology Program (NTP).

A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
Quartz (SiO <sub>2</sub> )	14808-60-7		CA

##### Legend

CA Carcinogenic

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
Quartz (SiO <sub>2</sub> )	14808-60-7	T
Quartz (SiO <sub>2</sub> )	14808-60-7	T

##### Legend

T Toxicity (ACGIH®)

## ZAR® Wood Patch - Red Oak

Version number: REV 6.0  
 Replaces version of: 2023-02-22 (REV 5)

Revision: 2023-12-15

### California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals			
Name acc. to inventory	CAS No	Remarks	Type of the toxicity
silica, crystalline		airborne particles of respirable size	cancer
nickel	7440-02-0	metallic	cancer
nickel	7440-02-0	Nickel refinery dust from the pyrometallurgical process	cancer
Talc containing asbestiform fibers	14807-96-6	Talc containing asbestiform fibers	cancer
1,4-dioxane	123-91-1		cancer
ethylene oxide	75-21-8		cancer
ethylene oxide	75-21-8		female
ethylene oxide	75-21-8		developmental, male
acetaldehyde	75-07-0		cancer
lead compounds			cancer
cobalt	7440-48-4	metal powder	cancer
mercury compounds			developmental

### Industry or sector specific available guidance(s)

#### NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	0	material that will not burn under typical fire conditions
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

#### NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	0	material that will not burn under typical fire conditions
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions

## ZAR® Wood Patch - Red Oak

Version number: REV 6.0  
 Replaces version of: 2023-02-22 (REV 5)

Revision: 2023-12-15

Category	Degree of hazard	Description
Special hazard		

### National inventories

Country	Inventory	Status
EU	REACH Reg.	not all ingredients are listed
US	TSCA	all ingredients are listed or exempt from listing
AU	AIIC	not all ingredients are listed
CA	DSL	all ingredients are listed or exempt from listing
CN	IECSC	not all ingredients are listed
EU	ECSI	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed or exempt from listing
MX	INSQ	not all ingredients are listed
NZ	NZIoC	not all ingredients are listed
PH	PICCS	all ingredients are listed or exempt from listing
TR	CICR	not all ingredients are listed
TW	TCSI	not all ingredients are listed
VN	NCI	not all ingredients are listed

#### Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NCI	National Chemical Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

### 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## ZAR® Wood Patch - Red Oak

Version number: REV 6.0  
 Replaces version of: 2023-02-22 (REV 5)

Revision: 2023-12-15

### SECTION 16: Other information, including date of preparation or last revision

#### Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
1.3	Details of the supplier of the safety data sheet: United Gilsonite Laboratories, Inc. 1396 Jefferson Avenue Dunmore PA 18509 United States  Telephone: +1 (570) 344-1202 Telefax: (570) 969-7634 e-mail: sales@ugl.com Website: http://www.ugl.com/	Details of the supplier of the safety data sheet: United Gilsonite Laboratories, Inc. - Sika 1396 Jefferson Avenue Dunmore PA 18509 United States  Telephone: +1 (570) 344-1202 Telefax: (570) 969-7634 e-mail: sales@ugl.com Website: http://www.ugl.com/	yes
2.1		Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200): change in the listing (table)	yes
2.1	The most important adverse physicochemical, human health and environmental effects: The product is combustible and can be ignited by potential ignition sources.		yes
2.2		- Pictograms: change in the listing (table)	yes
2.2		- Hazard statements: change in the listing (table)	yes
2.2		- Precautionary statements: change in the listing (table)	yes
2.3	Endocrine disrupting properties: Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0,1\%$ .	Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$ .	yes
3.2		Description of the mixture: change in the listing (table)	yes
5.2	Special hazards arising from the substance or mixture: In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.	Special hazards arising from the substance or mixture	yes
7.1	- Measures to prevent fire as well as aerosol and dust generation: Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.	- Measures to prevent fire as well as aerosol and dust generation: Use local and general ventilation. Use only in well-ventilated areas.	yes

## ZAR® Wood Patch - Red Oak

Version number: REV 6.0  
 Replaces version of: 2023-02-22 (REV 5)

Revision: 2023-12-15

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
7.1	Specific notes/details: Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.		yes
7.2	Managing of associated risks		yes
7.2	- Explosive atmospheres: Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.		yes
7.2	- Flammability hazards: Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.		yes
7.2	- Ventilation requirements: Use local and general ventilation. Ground/bond container and receiving equipment.		yes
7.2	- Packaging compatibilities: Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.		yes
9.1	Flash point: 49 °C at 1 atm	Flash point: 100 °C at 1 atm	yes
10.1	Reactivity: Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.	Reactivity: Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".	yes
10.1	If heated: Risk of ignition		yes
10.4	Conditions to avoid: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	Conditions to avoid: There are no specific conditions known which have to be avoided.	yes
10.4	Hints to prevent fire or explosion: Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.		yes
12.6	Endocrine disrupting properties: Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0,1\%$ .	Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$ .	yes
13.1	Waste treatment-relevant information: Solvent reclamation/regeneration.		yes
13.1	Waste treatment of containers/packages: Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.	Waste treatment of containers/packages: Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.	yes
14.1	UN number	UN number: not subject to transport regulations	yes

## ZAR® Wood Patch - Red Oak

Version number: REV 6.0  
 Replaces version of: 2023-02-22 (REV 5)

Revision: 2023-12-15

Section	Former entry (text/value)	Actual entry (text/value)	Safety-rel- evant
14.1	DOT: UN 1263		yes
14.1	IMDG-Code: UN 1263		yes
14.1	ICAO-TI: UN 1263		yes
14.2	DOT: Paint		yes
14.2	IMDG-Code: PAINT		yes
14.2	ICAO-TI: Paint		yes
14.3	DOT: 3		yes
14.3	IMDG-Code: 3		yes
14.3	ICAO-TI: 3		yes
14.4	DOT: III		yes
14.4	IMDG-Code: III		yes
14.4	ICAO-TI: III		yes
14.7	Particulars in the shipper's declaration: UN1263, Paint, 3, III		yes
14.7	Reportable quantity (RQ): 375,940 lbs (170,677 kg) (ammonia) (arsenic)		yes
14.7	Danger label(s): 3		yes
14.7		Danger label(s): change in the listing (table)	yes
14.7	Special provisions (SP): 367, B1, B52, B131, IB3, T2, TP1, TP29		yes
14.7	ERG No: 128		yes
14.7	Marine pollutant: -		yes
14.7	Danger label(s): 3		yes
14.7		Danger label(s): change in the listing (table)	yes
14.7	Special provisions (SP): 163, 223, 367, 955		yes
14.7	Excepted quantities (EQ): E1		yes

## ZAR® Wood Patch - Red Oak

Version number: REV 6.0  
 Replaces version of: 2023-02-22 (REV 5)

Revision: 2023-12-15

Section	Former entry (text/value)	Actual entry (text/value)	Safety-rel- evant
14.7	Limited quantities (LQ): 5 L		yes
14.7	EmS: F-E, <u>S-E</u>		yes
14.7	Stowage category: A		yes
14.7	Danger label(s): 3		yes
14.7		Danger label(s): change in the listing (table)	yes
14.7	Special provisions (SP): A3, A72, A192		yes
14.7	Excepted quantities (EQ): E1		yes
14.7	Limited quantities (LQ): 10 L		yes
14.2	UN proper shipping name	UN proper shipping name: not relevant	yes
14.3	Transport hazard class(es)	Transport hazard class(es): none	yes
14.4	Packing group	Packing group: not assigned	yes
14.7	Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information	Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information: Not subject to transport regulations.	yes
14.7	International Maritime Dangerous Goods Code (IMDG) - Additional information	International Maritime Dangerous Goods Code (IMDG) - Additional information: Not subject to IMDG.	yes
14.7	International Civil Aviation Organization (ICAO- IATA/DGR) - Additional information	International Civil Aviation Organization (ICAO- IATA/DGR) - Additional information: Not subject to ICAO-IATA.	yes
15.1		Toxic Substance Control Act (TSCA): not all ingredients are listed (ACTIVE)	yes
15.1		Hazardous Substance List (RI-RTK): change in the listing (table)	yes
15.1		Proposition 65 List of chemicals: change in the listing (table)	yes
15.1		NPCA-HMIS® III: change in the listing (table)	yes
15.1		NFPA® 704: change in the listing (table)	yes
15.1		National inventories: change in the listing (table)	yes

### Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).



## ZAR® Wood Patch - Red Oak

Version number: REV 6.0  
 Replaces version of: 2023-02-22 (REV 5)

Revision: 2023-12-15

### Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H226	Flammable liquid and vapor.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H320	Causes eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H350	May cause cancer.
H360F	May damage fertility.
H372	Causes damage to organs through prolonged or repeated exposure.
OSHA003	May form combustible dust concentrations in air.

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

### End of safety data sheet